

Application

Recessed wall luminaire with forward throw light distribution for the illumination of ground surfaces, stairs and pathways.

Materials

Clear safety glass with optical texture
BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Mechanically captive stainless steel fasteners
Stainless steel helicoils
Stainless steel screw clamps
High temperature silicone gasket
Silicone applied robotically to casting, plasma treated for increased adhesion
Composite installation housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 7.3lbs.

Electrical

Operating voltage 120V or 277V AC
Minimum start temperature -30° C
LED module wattage 20.0W
System wattage 27.0W
Controllability 0-10V, TRIAC, and ELV dimmable
Color rendering index Ra > 80
Luminaire lumens 2255lm
LED service life (L70) 60000hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:
CUS:

Type:

BEGA Product:

Project:


Modified:

Available options

CUS Custom finish
DALI-2 Digital addressable lighting interface
EMPK Integral emergency battery pack (30% output for 90 minutes)
FSC Fusing
MGU Marine grade undercoat
NTB Natural bronze (premium finish)
RAL RAL finish

Included (available for pre-shipment)

BB24573 Installation housing



Recessed wall luminaire · Asymmetric

		LED	A	B	C
B24575	ADA	20.0W	11 ³ / ₄	11 ³ / ₄	5 ¹ / ₈

