

**Application**

A wall mounted luminaire with light emission from one side and a symmetrical distribution. Can be arranged individually or in groups to serve a broad range of lighting applications.

**Materials**

Clear safety glass with optical texture  
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
 Silicone applied robotically to casting, plasma treated for increased adhesion  
 Stainless steel hardware  
 Pure anodized aluminum reflector

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65

**Weight:** 24.7 lbs.

**Electrical**

Operating voltage 120-277VAC  
 Minimum start temperature -20° C  
 LED module wattage 46.4 W  
 System wattage 56.0 W  
 Controllability 0-10V dimming down to 1%  
 Color rendering index Ra > 80  
 Luminaire lumens 4685 lm  
 LED service life (L70) 60000 hrs

**LED color temperature**

4000K (K4)  
 3500K (K35)  
 3000K (K3)  
 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

**Available colors**

Black (BLK) Bronze (BRZ)  
 Natural Bronze (NTB) Silver (SLV)  
 White (WHT) RAL:  
 CUS:

Type:

BEGA Product:

Project:

Modified:

**Available options**

CUS Custom finish  
 DALI-2 Enabled for DALI control system  
 ELV/TRIAC Electronic low voltage/TRIAC dimming  
 FSC Fusing  
 MGU Marine grade undercoat  
 NTB Natural bronze (premium finish)  
 RAL RAL Classic, matte finish



**Wall luminaire · Light emission on one side · symmetrical**

	LED	A	B	C
<b>B24587</b>	46.4 W	48 1/2	4 1/8	5 1/4

