

Wall luminaire · Narrow beam upward · Narrow beam downward

BEGA

Application

Designed to provide general illumination and visual interest for interior and exterior locations. A narrow beam light distribution in both directions is ideal for general illumination of pathways and corridors, while highlighting various architectural features and creating patterns of light.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Galvanized zinc-plated mounting bracket
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 64

Weight: 7.3 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage33.0 W
- System wattage38.4 W
- Controllability0-10V dimming down to 1%
- Color rendering indexRa > 80
- Luminaire lumens3031 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- Natural Bronze (NTB)
- CUS:
- Bronze (BRZ)
- White (WHT)
- RAL:

Type:


BEGA Product:

Project:

Modified:

Available options

- CUSCustom finish
- DALIDigital addressable lighting interface
- FROFrosted lens
- FSCFusing
- MGUMarine grade undercoat
- NTBNatural bronze (premium finish)
- RALRAL finish
- SRGSurge protection
- SWBCSurface wiring box cover
- UPOUplight only



Wall luminaire · Narrow beam upward · Narrow beam downward					
	LED		A	B	C
B24593	33.0 W	16°	5 ⁷ / ₈	10 ⁵ / ₈	6 ⁷ / ₈

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805)684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2025 Updated 08/12/25