

Wall luminaire · Very narrow beam upward · Narrow downward

BEGA

Application

Designed to provide general illumination and visual interest for interior and exterior locations. A narrow beam light distribution downward is ideal for general illumination of pathways and corridors, while a very narrow distribution upward is ideal for highlighting various architectural features and creating patterns of light.

Materials

Clear safety glass  
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners  
Silicone applied robotically to casting, plasma treated for increased adhesion  
Galvanized zinc-plated mounting bracket  
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 64

Weight: 7.5 lbs.

Electrical

Operating voltage 120-277VAC  
Minimum start temperature -30° C  
LED module wattage 33.0W  
System wattage 38.4W  
Controllability 0-10V dimming down to 1%  
Color rendering index Ra > 80  
Luminaire lumens 1888lm  
LED service life (L70) 60000hrs

LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)  
Silver (SLV) White (WHT)  
Natural Bronze (NTB) RAL:  
CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

CUS Custom finish  
FSC Fusing  
MGU Marine grade undercoat  
NTB Natural bronze (premium finish)  
RAL RAL finish



Wall luminaire · Very narrow beam upward · Narrow downward

	LED	□	A	B	C
B24597	33.0W	9°/20°	5 <sup>7</sup> / <sub>8</sub>	10 <sup>5</sup> / <sub>8</sub>	6 <sup>7</sup> / <sub>8</sub>



BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805)684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com  
© copyright BEGA 2025 Updated 08/12/25