


BEGA

Photometric Filename: 24600.IES

TEST: BE_24600
TEST LAB: BEGA
DATE: 11/9/2016
LUMINAIRE: 24 600
LAMP: 9.7W LED




Characteristics


Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	833
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	69
Total Luminaire Watts	12
Ballast Factor	1.00
CIE Type	Semi-Direct
Spacing Criterion (0-180)	1.34
Spacing Criterion (90-270)	1.34
Spacing Criterion (Diagonal)	1.52
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	0.72 ft
Luminous Width (90-270)	0.72 ft
Luminous Height	0.15 ft

Zonal Lumen Summary

Zone	Lumens
0-10	18.55
10-20	53.23
20-30	82.73
30-40	105.02
40-50	117.68
50-60	118.17
60-70	101.59
70-80	68.12
80-90	39.53
90-100	33.28
100-110	32.99
110-120	26.98
120-130	18.96
130-140	10.90
140-150	4.48
150-160	0.83
160-170	0.04
170-180	0.04



Ceiling mount - isofootcandle grid on floor
Mounting Height = 10 ft. Grid Spacing = 10 ft.



Wall mount - isofootcandle grid on floor
Mounting Height = 5 ft. Grid Spacing = 5 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2018

7/25/2018