

Application

Designed for accent lighting of columns, walls, and façades. The symmetric very wide beam distributions are ideal for general illumination of pathways and corridors while highlighting architectural features and producing patterns of light on the installation surface.

Materials

Clear safety glass with matte finish
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
Stainless steel hardware
Silicone applied robotically to casting, plasma treated for increased adhesion
Galvanized steel mounting strap
Pure anodized aluminum reflector surface

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 5.8 lbs.

Electrical

Operating voltage 120-277VAC
Minimum start temperature -30° C
LED module wattage 16.8W
System wattage 20.0W
Controllability 0-10V, TRIAC, and ELV dimmable
Color rendering index Ra > 90
Luminaire lumens 1880 lm
LED service life (L70) 60000hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:
CUS:

Type:

BEGA Product:

Project:


Modified:

Available options

CUS Custom finish
DALI-2 Digital addressable lighting interface
FSC Fusing
MGU Marine grade undercoat
NTB Natural bronze (premium finish)
RAL RAL finish

Included (available for pre-shipment)

B19542 Narrow opening wiring box



Wall luminaires · Very wide beam in both directions

	LED	β	A	B	C
B24617	16.8W	72°	4 1/2	7 5/8	6 1/8

