

Wall luminaire · Light emission on two sides · symmetrical and asymmetrical

**BEGA**

**Application**

Wall luminaire with two-sided light emission, delivering asymmetrical distribution above and symmetrical distribution below. Suited to individual placement or grouped arrangements across a broad range of architectural lighting applications.

**Materials**

Clear safety glass with optical texture  
 Marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy  
 High temperature silicone gasket  
 Silicone applied robotically to casting, plasma treated for increased adhesion  
 Pure anodized aluminum reflector surface

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65

**Weight:** 13.2 lbs.

**Electrical**

Operating voltage 120-277V AC  
 Minimum start temperature  $-20^{\circ}\text{C}$   
 LED module wattage 46.4 W  
 System wattage 56.0 W  
 Controllability 0-10V dimming down to 1%  
 Color rendering index  $Ra > 80$   
 Luminaire lumens 4351 lm  
 LED service life (L70) 60000 hrs

**LED color temperature**

4000K (K4)  
 3500K (K35)  
 3000K (K3)  
 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

**Available colors**

Black (BLK)	Bronze (BRZ)
Natural Bronze (NTB)	Silver (SLV)
White (WHT)	RAL:
CUS:	

Type:

BEGA Product:

Project:

Modified:

**Available options**

CUS	Custom finish
DALI-2	Enabled for DALI control system
ELV/TRIAC	Electronic low voltage/TRIAC dimming
FSC	Fusing
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL Classic, matte finish



**Wall luminaire · Light emission on two sides · symmetrical and asymmetrical**

	LED	A	B	C
<b>B24643</b>	46.4 W	24 <sup>7</sup> / <sub>8</sub>	4 <sup>1</sup> / <sub>8</sub>	4 <sup>1</sup> / <sub>4</sub>



**BEGA** 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com