

Application

Compact ceiling mounted downlights designed for down lighting atriums, canopies, passages and other interior and exterior locations.

Materials

Clear safety glass
 Marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
 Silicone applied robotically to casting, plasma treated for increased adhesion
 BEGA Hybrid Optics®
 Pure anodized aluminum reflector surface
 Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 8.59lbs.

Electrical

Operating voltage 120-277VAC
 LED module wattage 71.1 W
 System wattage 76.0W
 Controllability 0-10V dimmable
 Color rendering index Ra > 80
 Luminaire lumens 9406 lm
 LED service life (L70) 60000 hrs

LED color temperature

4000K (K4)
 3500K (K35)
 3000K (K3)
 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
 Silver (SLV) White (WHT)
 RAL: CUS:

Type:

BEGA Product:

Project:

Modified:

Available options

CUS Custom finish
 DALI-2 Enabled for DALI control system
 FRO Frosted lens
 FSC Fusing
 MGU Marine grade undercoat
 NTB Natural bronze (premium finish)
 RAL RAL Classic, matte finish



Surface mounted downlight · Symmetric wide beam

	LED	β	A	B
B24657	71.1 W	35	8 ^{7/8}	7 ^{1/2}

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com