

Application
BEGA Ultradark Optics® provide targeted illumination with an extremely quiet aperture. An internal louver with ultra-black coating for maximum light absorption is ideal for interior or exterior spaces where the lighting effect takes center stage, and the luminaire disappears into the ceiling. The inside coating has a total hemispherical reflectance (THR) below 1% in the visible spectrum.

Materials
Clear UV-stabilized acrylic diffuser with anti-glare finish
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Stainless steel screw clamps
Galvanized steel rough in ceiling pan with through wiring junction box
BEGA Ultradark Optics®

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 3.8 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	18.3W
System wattage	21.0W
Controllability	0-10V dimming down to 1%
Color rendering index	Ra > 90
Luminaire lumens	1637 lm
LED service life (L70)	60000hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors


Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:
BEGA Product:
Project:
Modified:

Available options

CUS	Custom finish
DALI-2	Enabled for DALI control system
ELV/TRIAC	Electronic low voltage/TRIAC dimming
FSC	Fusing
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL Classic, matte finish

Included (available for pre-shipment)
CP24722 Ceiling Pan (0-10V dimmable down to 0.1%)



Downlight · Symmetric · Narrow beam						
	LED	β	A	B	C	D
B24722	18.3W	22°	6 7 / ₈	0 1 / ₄	5 7 / ₈	18

