

Application

Designed for accent lighting of columns, walls, and façades. The symmetric narrow beam distribution is ideal for highlighting various architectural features and producing patterns of light on the installation surface. Able to be installed with light output upward or downward.

Materials

- Clear safety glass with matte finish
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Stainless steel hardware
- Galvanized steel mounting strap
- Pure anodized aluminum reflector surface

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 2.65 lbs.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-20° C
- LED module wattage3.9W
- System wattage6.0W
- Controllability0-10V dimming down to 0.1%
- Color rendering indexRa > 90
- Luminaire lumens162lm
- LED service life (L70)60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- Natural Bronze (NTB)
- CUS:
- Bronze (BRZ)
- White (WHT)
- RAL:

Type:

BEGA Product:

Project:


Modified:

Available options

- CUS Custom finish
- DALI-2 Enabled for DALI control system
- MGU Marine grade undercoat
- NTB Natural bronze (premium finish)
- RAL RAL Classic, matte finish

Included (available for pre-shipment)

- B19542 Narrow opening wiring box



Wall luminaires · Narrow beam upward or downward

	LED	β	A	B	C
B24733	3.9W	22°	3 1/8	6 1/4	4 1/8

