


BEGA

Photometric Filename: 24814.IES

TEST: BE_24814
TEST LAB: BEGA
DATE: 9/8/2016
LUMINAIRE: 24 814
LAMP: 17.8W LED




Characteristics


NEMA Type	4 H x 5 V
Maximum Candela	2274.1
Maximum Candela Angle	0 H 33 V
Horizontal Beam Angle (50%)	51.1
Vertical Beam Angle (50%)	47.9
Horizontal Field Angle (10%)	68.8
Vertical Field Angle (10%)	70.6
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Beam Lumens	1003
Beam Efficiency	N.A.
Field Lumens	1423
Field Efficiency	N.A.
Spill Lumens	157
Luminaire Lumens	1580
Total Efficiency	N.A.
Total Luminaire Watts	22

Zonal Lumen Summary

Zone	Lumens
0-10	57.09
10-20	188.10
20-30	340.69
30-40	419.73
40-50	339.93
50-60	161.25
60-70	46.82
70-80	12.60
80-90	1.86
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00



Mounting Height = 10 ft. Grid Spacing = 5 ft.



In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2018

1/23/2018