

Application

Wall mounted luminaire with asymmetric light distribution, ideal for illuminating horizontal surfaces from vertical mounting surfaces.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Silicone applied robotically to casting, plasma treated for increased adhesion
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Integral surge protector
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 11.5 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage55.3 W
- System wattage61.0 W
- Controllability0-10V dimming down to 1%
- Color rendering indexRa > 80
- Luminaire lumens6672 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)


Silver (SLV)

Natural Bronze (NTB)

CUS:
- Bronze (BRZ)

White (WHT)

RAL:



Wall luminaire · Asymmetric

	LED	A	B	C	D
B24816	55.3 W	8 7/8	4	19 1/4	5 1/4

Type:

BEGA Product:

Project:

Modified:

Available options

- 96112

CUS

FSC

MGU

NTB

RAL
- Surface wiring box painted to match fixture. 1/2" or 3/4" side conduit or rear conduit available, see submittal drawing. Replaces standard mounting.

Custom finish

Fusing

Marine grade undercoat

Natural bronze (premium finish)

RAL finish

