

Application

This unshielded wall luminaire delivers a blend of functional illumination and architectural presence. Ideal for entryways, columns, or façades, it enhances wayfinding, highlights structure, and creates visual rhythm across exterior spaces.

Materials

- Hand-blown opal glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Stainless steel hardware
- Galvanized steel mounting strap

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 3.8 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	4.7 W
System wattage	7.4 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	559lm
LED service life (L70)	60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Natural Bronze (NTB)	Silver (SLV)
White (WHT)	RAL:
CUS:	

Type:

BEGA Product:

Project:


Modified:

Available options

CUS	Custom finish
DALI-2	Enabled for DALI control system
DCP	Decorative cover plate - For use with standard single-gang wiring box
FSC	Fusing
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL Classic, matte finish

Included (available for pre-shipment)

B19542	Narrow opening wiring box
--------	---------------------------



Wall luminaire · Unshielded				
	LED	A	B	C
B24849	4.7 W	4 <sup>3</sup> / <sub>8</sub>	9 <sup>3</sup> / <sub>4</sub>	6

