

Application

Wall luminaires with shielded light distribution. The shape of the lantern is unmatched in its diversity. These luminaires are particularly suitable for illuminating areas in front of the mounting surface such as courtyards or alongside and above doors.

Materials

Hand-blown three-ply opal glass
Aluminum housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 44

Weight: 2.2 lbs.

Electrical

Operating voltage 120-277V AC
Minimum start temperature -30° C
LED module wattage 3.0W
System wattage 5.0W
Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 375lm
LED service life (L70) 60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

BEGA Black polyester powder coat finish. Custom colors not available.

Available colors

Black (BLK)

Type:


BEGA Product:

Project:

Modified:

Available options

CUS Custom finish
DALI-2 Enabled for DALI control system
MGU Marine grade undercoat
NTB Natural bronze (premium finish)
RAL RAL Classic, matte finish



| Wall luminaire · Shielded | | | | |
|---------------------------|------|---|-------|--------|
| | LED | A | B | C |
| B31014 | 3.0W | 7 | 8 1/2 | 10 1/4 |
| | | | | 3 1/8 |

