

Application

A ceiling and wall luminaire with copper and opal glass. Backlight onto the wall or ceiling surface creates a contrast between the opal glass, the shield, and the mounting surface when illuminated.

Materials

- Three-ply opal glass with satin matte finish
- A380 aluminum alloy
- 99.9% pure copper
- High temperature silicone gasket
- Stainless steel mounting plate

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 6.8 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- Maximum ambient temperature50° C
- LED module wattage14.2 W
- System wattage18.0 W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens1489 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details


Finish

Natural copper. Time and weather factors will create the natural patina of copper.

Type:  
BEGA Product:  
Project:  
Modified:

Available options

- DALI Digital addressable lighting interface
- ELV/TRIAC Electronic low voltage/TRIAC
- FSC Fusing



Ceiling and wall luminaire · Opal glass					
		LED	A	B	C
B31042	ADA	14.2 W	12 <sup>7</sup> / <sub>8</sub>	3 <sup>5</sup> / <sub>8</sub>	9 <sup>7</sup> / <sub>8</sub>

