

Application

Wall luminaires with partially shielded light distribution. A combination of materials in perfect harmony with this classic luminaire shape. Whether as single luminaires or arranged in groups, these luminaires are perfect architectural elements.

Materials

- Hand-blown three-ply opal glass
- 99.9% pure copper
- High-strength, free machining C38500 brass
- Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 44

Weight: 14.3 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage22.0 W
- System wattage25.5 W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens1340 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish


Natural cast bronze and copper. Time and weather factors will create the natural patina of bronze and copper.

Type:

BEGA Product:

Project:

Modified:



Cast bronze and copper wall luminaire · Unshielded

	LED	A	B	C	D
B31087	22.0 W	17 ³ / ₄	25 ³ / ₈	19 ⁵ / ₈	5 ⁷ / ₈

