

Application

Wall luminaires with unshielded light distribution. These luminaires are ideally suited for illuminating entrances, arcades and walkways. Clear-cut lines and high-quality materials result in elements of architectural design that are both striking and long lasting.

Materials

- Hand-blown three-ply opal glass
- 99.9% pure copper
- High-strength, free machining C38500 brass
- Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 44

Weight: 11.0 lbs.

Electrical

- | | |
|---------------------------|----------------|
| Operating voltage | 120-277V AC |
| Minimum start temperature | -30° C |
| LED module wattage | 22.0 W |
| System wattage | 25.5 W |
| Controllability | 0-10V dimmable |
| Color rendering index | Ra > 80 |
| Luminaire lumens | 1540 lm |
| LED service life (L70) | 60000 hrs |

LED color temperature


- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Natural copper with brass. Time and weather factors will create the natural patina of copper.

Type:
BEGA Product:
Project:
Modified:



Copper and brass wall luminaire · Unshielded				
	LED	A	B	C
B31095	22.0 W	4 1/4	25 3/8	6 1/2
				4 3/8

