

Application

Wall luminaires with unshielded light distribution. These luminaires are ideally suited for illuminating entrances, arcades and walkways. Clear-cut lines and high-quality materials result in elements of architectural design that are both striking and long lasting.

Materials

Hand-blown three-ply opal glass  
99.9% pure copper

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 44

Weight: 5.5 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	3.2 W
System wattage	5.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	192 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Natural copper. Time and weather factors will create the natural patina of copper.

Type:


BEGA Product:

Project:

Modified:

Available options

DALI-2      Enabled for DALI control system



Cast bronze, copper and brass wall luminaire · Unshielded

	LED	A	B	C	D
B31098	3.2 W	6 3/4	14 1/8	4	3 1/2

