

Application

Wall mount luminaires with shielded light distribution and tool-less entry. These luminaires are extremely robust, made of cast bronze, and resemble maritime portholes, their shape is defined by simple functional elements.

Materials

Pressed crystal glass with white ceramic coating on one side
High-strength, C90700 bronze
High-strength, free machining C38500 brass
High temperature silicone gasket
Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 10.9lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	6.3W
System wattage	8.5W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	218lm
LED service life (L70)	60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Natural cast bronze with brass. Time and weather factors will create the natural patina of bronze.

Type:


BEGA Product:

Project:

Modified:

Available options

DALI-2 Enabled for DALI control system



Cast bronze wall luminaire · Shielded · Tool-less entry

	LED	A	B	C
B31120	6.3W	8 1/2	7 7/8	6 3/8

