

Application

Wall mount luminaires with shielded light distribution and tool-less entry. These luminaires are extremely robust, made of cast bronze, and resemble maritime portholes, their shape is defined by simple functional elements.

Materials

- Pressed crystal glass with white ceramic coating on one side
- High-strength, C90700 bronze
- High-strength, free machining C38500 brass
- High temperature silicone gasket
- Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 16.0 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	7.9W
System wattage	10.0W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 80
Luminaire lumens	257 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish


Natural cast bronze with brass. Time and weather factors will create the natural patina of bronze.

Type:

BEGA Product:

Project:

Modified:



Cast bronze wall luminaire · Shielded · Tool-less entry				
	LED	A	B	C
B31148	7.9W	10 ⁷ / ₈	10 ⁷ / ₈	5 ¹ / ₄