## Application

Wall mount luminaires with unshielded light and tool-less entry. These luminaires are extremely robust, made of cast bronze, and resemble maritime portholes, their shape is defined by simple functional elements.

#### Materials

Pressed crystal glass with white ceramic coating on one side

High-strength, C90700 bronze

High-strength, free machining C38500 brass

High temperature silicone gasket

Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 65

Weight: 8.4 lbs.

Electrical

Operating voltage 120-277V AC
Minimum start temperature -30° C
LED module wattage 6.3 W
System wattage 8.5 W

System wattage 8.5 W Controllability 0-10\

Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 340 lm
LED service life (L70) 60000 hrs

## LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

### Finish

Natural cast bronze with brass. Time and weather factors will create the natural patina of bronze.

Type:


**BEGA Product:** 

Project: Modified:

# Available options

DALI-2 Enabled for DALI control system





Cast bronze wall luminaire · Unshielded · Tool-less entry

	LED	А	В	С
B31159	6.3 W	81/2	77/。	63/。