

Application

A series of wall luminaires with shielded light distribution. The shape of the lantern is unmatched in its diversity. These luminaires are particularly suitable for illuminating areas directly below the mounting surface such as courtyards or alongside and above doors.

Materials

Hand-blown three-ply opal glass  
99.9% pure copper  
High-strength, free machining C38500 brass  
Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 44

Weight: 4.9 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	6.3W
System wattage	8.6W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	286lm
LED service life (L70)	60000 hrs

LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Natural copper. Time and weather factors will create the natural patina of copper.

Type:


BEGA Product:

Project:

Modified:

Available options

DALI-2      Enabled for DALI control system



Copper wall luminaire · Unshielded

	LED	A	B	C	D
B31171	6.3W	9 1/4	8 1/4	14 1/2	4 3/8