

Application

Wall luminaires with unshielded light distribution. A combination of materials in perfect harmony with this classic luminaire shape. Whether as single luminaires or arranged in groups, these luminaires are perfect architectural elements.

Materials

Hand-blown three-ply opal glass  
99.9% pure copper  
High-strength, C90700 bronze

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 44

Weight: 13.4 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	3.9W
System wattage	11.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	537 lm
LED service life (L70)	60000hrs

LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish


Natural cast bronze and copper. Time and weather factors will create the natural patina of bronze and copper.

Type:

BEGA Product:

Project:

Modified:



Cast bronze and copper wall luminaire · Unshielded

	LED	A	B	C	D
B31218	3.9W	9 <sup>7</sup> / <sub>8</sub>	21 <sup>1</sup> / <sub>8</sub>	12 <sup>1</sup> / <sub>8</sub>	5 <sup>1</sup> / <sub>8</sub>

Available options

DALI-2      Enabled for DALI control system

