

Application

Ceiling and wall luminaires with unshielded light distribution and guard. Whether as single luminaires or arranged in groups, these luminaires are robust and perfect architectural elements.

Materials

Clear safety glass with white ceramic coating
99.9% pure copper
High temperature silicone gasket

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 64

Weight: 4.0 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	6.3 W
System wattage	8.3 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	362 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Natural copper with cast bronze and brass. Time and weather factors will create the natural patina of copper and bronze.

Type:


BEGA Product:

Project:

Modified:

Available options

DALI-2 Enabled for DALI control system



Ceiling and wall luminaire · Unshielded			
	LED	A	B
B31327	6.3 W	8 ⁵ / ₈	5 ¹ / ₈

