

Application

Ceiling and wall luminaires with unshielded light distribution. Whether as single luminaires or arranged in groups, these luminaires are robust and perfect architectural elements.

Materials

Pressed crystal glass with white ceramic coating on one side
99.9% pure copper
High-strength, free machining C38500 brass

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 64

Weight: 5.3 lbs.

Electrical

| | |
|---------------------------|----------------|
| Operating voltage | 120-277V AC |
| Minimum start temperature | -30° C |
| LED module wattage | 12.6 W |
| System wattage | 14.6 W |
| Controllability | 0-10V dimmable |
| Color rendering index | Ra > 80 |
| Luminaire lumens | 819 lm |
| LED service life (L70) | 60000 hrs |

LED color temperature


- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Natural copper with cast bronze and brass. Time and weather factors will create the natural patina of copper and bronze.

Type:
BEGA Product:
Project:
Modified:



| Ceiling and wall luminaire · Unshielded | | | |
|---|--------|----|-------|
| | LED | A | B |
| B31394 | 12.6 W | 11 | 5 5/8 |