

Application

Recessed wall luminaire with shielded light distribution that is ideal for glare-free illumination of ground surfaces, building entrances, stairs and footpaths. Separate installation housing allows for seamless coordination into construction and easy maintenance.

Materials

- Clear safety glass with white ceramic coating
- Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
- BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection
- Mechanically captive stainless steel fasteners
- Stainless steel screw clamps
- Composite installation housing
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 2.2 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-40° C
LED module wattage	3.8W
System wattage	7.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	64 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:

BEGA Product:

Project:


Modified:

Available options

AMB	Amber LED
CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL Classic, matte finish

Included (available for pre-shipment)

BB24065	Installation housing
---------	----------------------



Recessed wall luminaire · Shielded				
	LED	A	B	C
B33019	3.8W	12 1/2	2 3/4	5

