

Application
Recessed wall luminaires with asymmetric light distribution ideal for the glare-free illumination of ground surfaces, building entrances, stairs and footpaths.

Materials
Clear safety glass with optical texture
Corrosion-resistant 304 grade stainless steel
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Aluminum installation housing
Pure anodized aluminum reflector surface

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 4.0lbs.

Electrical
Operating voltage 120-277VAC
Minimum start temperature -30° C
LED module wattage 5.9W
System wattage 6.0W
Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 570lm
LED service life (L70) 60000hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
#4 brushed stainless steel. Custom colors are not available.

Type:
BEGA Product:
Project:
Modified:

Available options
DALI-2 Enabled for DALI control system

Included (available for pre-shipment)
BB3021LED Installation housing



Recessed wall luminaire · Asymmetric				
		LED	A	B
B33021	ADA	5.9W	8 ¹ / ₄	4 ⁵ / ₈