

Application

Recessed wall luminaire with asymmetric light distribution that is ideal for the illumination of ground surfaces, building entrances, stairs and footpaths. Separate installation housing allows for seamless coordination into construction and easy maintenance.

Materials

BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection  
Composite installation housing  
Pure anodized aluminum reflector

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 65

**Weight:** 1.5 lbs.

Electrical

|                           |                |
|---------------------------|----------------|
| Operating voltage         | 120-277V AC    |
| Minimum start temperature | -40° C         |
| LED module wattage        | 4.1 W          |
| System wattage            | 6.0 W          |
| Controllability           | 0-10V dimmable |
| Color rendering index     | Ra > 90        |
| Luminaire lumens          | 231 lm         |
| LED service life (L70)    | 60000 hrs      |

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

|                      |              |
|----------------------|--------------|
| Black (BLK)          | Bronze (BRZ) |
| Silver (SLV)         | White (WHT)  |
| Natural Bronze (NTB) | RAL:         |
| CUS:                 |              |

Type:

BEGA Product:

Project:


Modified:

Available options

|     |                                 |
|-----|---------------------------------|
| AMB | Amber LED                       |
| CUS | Custom finish                   |
| FSC | Fusing                          |
| MGU | Marine grade undercoat          |
| NTB | Natural bronze (premium finish) |
| RAL | RAL finish                      |

Included (available for pre-shipment)

|         |                      |
|---------|----------------------|
| BB24063 | Installation housing |
|---------|----------------------|



| Recessed wall luminaire · Directed light |       |                               |                               |   |
|------------------------------------------|-------|-------------------------------|-------------------------------|---|
|                                          | LED   | A                             | B                             | C |
| <b>B33053</b>                            | 4.1 W | 6 <sup>5</sup> / <sub>8</sub> | 2 <sup>3</sup> / <sub>4</sub> | 5 |

