

Application
Recessed wall luminaire with directed light ideal for the illumination of wide ground surfaces, stairs and footpaths. Separate installation housing allows for seamless coordination into construction and easy maintenance.

Materials
BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 5.5 lbs.

Electrical	
Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	16.8W
System wattage	20.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	1470lm
LED service life (L70)	60000hrs

LED color temperature	
4000K (K4)	
3500K (K35)	
3000K (K3)	
2700K (K27)	

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details


Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors	
Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:
BEGA Product:
Project:
Modified:

Available options	
CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL finish

Included (available for pre-shipment)
BB24061 Installation housing



Recessed wall luminaire · Directed light				
	LED	A	B	C
B33067	16.8W	16 1/2	5	5 1/2

