

Application

Recessed wall luminaire with unshielded light distribution for the illumination of ground surfaces, building entrances, stairs and footpaths. Separate installation housing allows for seamless coordination into construction and easy maintenance.

Materials

Clear safety glass with white ceramic coating
 Marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
 BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection
 Stainless steel screw clamps
 Silicone applied robotically to casting, plasma treated for increased adhesion
 High temperature silicone gasket
 Mechanically captive stainless steel fasteners
 Composite installation housing

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 6.2 lbs.

Electrical

Operating voltage 120-277V AC
 Minimum start temperature -30°C
 LED module wattage 20.5W
 System wattage 24.0W
 Controllability 0-10V dimmable
 Color rendering index $R_a > 80$
 Luminaire lumens 1719lm
 LED service life (L70) 60000hrs

LED color temperature

4000K (K4)
 3500K (K35)
 3000K (K3)
 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
 Silver (SLV) White (WHT)
 Natural Bronze (NTB) RAL:
 CUS:



Recessed wall luminaire · Unshielded

	LED	A	B	C
B33159	20.5W	20 1/2	5	5 1/2

Type:

BEGA Product:

Project:

Modified:

Available options

CUS Custom finish
 FSC Fusing
 MGU Marine grade undercoat
 NTB Natural bronze (premium finish)
 RAL RAL finish

Included (available for pre-shipment)

BB24062 Installation housing

