

**Application**

Recessed wall luminaire with unshielded light to be used as location luminaires for means of way finding. Separate installation housing allows for seamless coordination into construction and easy maintenance.

**Materials**

Clear safety glass with white ceramic coating on one side  
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
 BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection  
 Mechanically captive stainless steel fasteners  
 Stainless steel screw clamps  
 Composite installation housing

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65

**Weight:** 1.8 lbs.

**Electrical**

Operating voltage 120-277V AC  
 Minimum start temperature -40° C  
 LED module wattage 2.7 W  
 System wattage 5.0W  
 Controllability 0-10V dimmable  
 Color rendering index Ra > 80  
 Luminaire lumens 239lm  
 LED service life (L70) 60000 hrs

**LED color temperature**

4000K (K4)  
 3500K (K35)  
 3000K (K3)  
 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

**Available colors**

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:

BEGA Product:

Project:

Modified:

**Available options**

CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
RAL	RAL finish

**Included (available for pre-shipment)**

BB24064 Installation housing



**Recessed wall luminaire · Location luminaire**

	LED	A	B	C
<b>B33163</b>	2.7 W	10 <sup>1</sup> / <sub>6</sub>	2 <sup>1</sup> / <sub>4</sub>	5