

Application

Recessed wall luminaire with unshielded light to be used as location luminaires for means of way finding. Separate installation housing allows for seamless coordination into construction and easy maintenance.

Materials

- Clear safety glass with white ceramic coating
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection
- Mechanically captive stainless steel fasteners
- Stainless steel screw clamps
- Composite installation housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 2.1 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-40° C
- LED module wattage3.8W
- System wattage6.0W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens329lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)

Silver (SLV)

Natural Bronze (NTB)

CUS:
- Bronze (BRZ)

White (WHT)

RAL:

Type:
BEGA Product:
Project:
Modified:

Available options

- AMB

CUS

FSC

MGU

NTB

RAL
- Amber LED

Custom finish

Fusing

Marine grade undercoat

Natural bronze (premium finish)

RAL Classic, matte finish

Included (available for pre-shipment)

- BB24065
- Installation housing



Recessed wall luminaire · Location luminaire				
	LED	A	B	C
B33166	3.8W	12 1/2	2 3/4	5

