

Application

Recessed wall luminaire with unshielded light that has a directing and guiding light effect. The illuminance level on the lit surface is lower, but the ambient brightness is greater with increased vertical illuminance.

Materials

- Clear safety glass with white ceramic coating
- Corrosion-resistant 304 grade stainless steel
- Die-cast aluminum
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Stainless steel screw clamps
- Aluminum installation housing

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 2.2 lbs.

Electrical

LED module wattage	2.1 W
System wattage	6.2 W
Color rendering index	Ra > 80
Luminaire lumens	41 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:

BEGA Product:

Project:

Modified:


Available accessories

B19591 Remote driver box · Static white

See individual accessory spec sheet for details.

Included (available for pre-shipment)

BB2100LED Installation housing



Recessed wall luminaire · Unshielded · 24V DC				
		LED	A	B
B33200	ADA	2.1 W	3 1/8	4