

Application
Recessed wall luminaire with unshielded light that has a directing and guiding light effect. The illuminance level on the lit surface is lower, but the ambient brightness is greater with increased vertical illuminance.

- Materials**
- Clear safety glass with white ceramic coating
 - Corrosion-resistant 304 grade stainless steel
 - Die-cast aluminum
 - High temperature silicone gasket
 - Mechanically captive stainless steel fasteners
 - Stainless steel screw clamps
 - Aluminum installation housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 4.0 lbs.

Electrical	
Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	4.0W
System wattage	6.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	176lm
LED service life (L70)	60000 hrs


- LED color temperature**
- 4000K (K4)
 - 3500K (K35)
 - 3000K (K3)
 - 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
#4 brushed stainless steel. Custom colors are not available.

Type:
BEGA Product:
Project:
Modified:

Included (available for pre-shipment)
BB3309LED Installation housing



Recessed wall luminaire · Unshielded				
		LED	A	B
B33309	ADA	4.0W	8 ¹ / ₄	4 ⁵ / ₈