

Application

The exceptional material thickness and strength of crystal glass provides this luminaire with robustness and defines its character. Arranged individually or in groups, they are great design elements for a host of lighting applications.

Materials

Pressed crystal glass with white ceramic coating on one side
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 High temperature silicone gasket
 Mechanically captive stainless steel fasteners
 Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 3.2 lbs.

Electrical

Operating voltage 120-277VAC
 Minimum start temperature -30° C
 LED module wattage 4.3W
 System wattage 11.0W
 Controllability 0-10V dimmable
 Color rendering index Ra > 80
 Luminaire lumens 216lm
 LED service life (L70) 60000hrs

LED color temperature

4000K (K4)
 3500K (K35)
 3000K (K3)
 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
 Silver (SLV) White (WHT)
 Natural Bronze (NTB) RAL:
 CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

CUS Custom finish
 MGU Marine grade undercoat
 NTB Natural bronze (premium finish)
 RAL RAL finish



Impact-resistant wall luminaire · Shielded on one side

| | LED | A | B | C |
|---------------|------|------------------|------------------|------------------|
| B33327 | 4.3W | 5 ^{5/8} | 4 ^{3/4} | 4 ^{3/4} |

