

Application

This wall luminaire has light output in two directions. It is ideal for upward and downward lighting effects for interior and exterior locations. Arranged individually or in groups, this is a great design element for a host of lighting applications.

Materials

Clear safety glass with white ceramic coating
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Silicone applied robotically to casting, plasma treated for increased adhesion

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 64

Weight: 2.0 lbs.

Electrical

Operating voltage120-277V AC
Minimum start temperature-40° C
LED module wattage3.9 W
System wattage6.0 W
Controllability0-10V dimmable
Color rendering indexRa > 90
Luminaire lumens247 lm
LED service life (L70)60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)Bronze (BRZ)
Silver (SLV)White (WHT)
Natural Bronze (NTB)RAL:
CUS:

Type:

BEGA Product:

Project:


Modified:

Available options

CUSCustom finish
MGUMarine grade undercoat
NTBNatural bronze (premium finish)
RALRAL finish

Included (available for pre-shipment)

B19545Narrow opening wiring box



Wall luminaire · Light emission on two sides

	LED	A	B	C
B33340	3.9 W	7 7/8	2 1/8	4 3/4

