

**Application**

This wall luminaire has a shielded light source with output in two directions. It is ideal for upward and downward lighting effects for interior and exterior locations. Arranged individually or in groups, this is a great design element for a host of lighting applications.

**Materials**

Pressed crystal glass with white ceramic coating on one side  
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
 High temperature silicone gasket  
 Mechanically captive stainless steel fasteners  
 Galvanized zinc-plated mounting bracket

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65

**Weight:** 9.5 lbs.

**Electrical**

Operating voltage                    120, 240 or 277VAC  
 Minimum start temperature       -30° C  
 LED module wattage                11.8W  
 System wattage                        14.0W  
 Controllability                        0-10V dimmable  
 Color rendering index                Ra > 80  
 Luminaire lumens                      846lm  
 LED service life (L70)               60000hrs

**LED color temperature**

4000K (K4)  
 3500K (K35)  
 3000K (K3)  
 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

**Available colors**

Black (BLK)                                Bronze (BRZ)  
 Silver (SLV)                                White (WHT)  
 Natural Bronze (NTB)                    RAL:  
 CUS:

Type:


BEGA Product:

Project:

Modified:

**Available options**

CUS                    Custom finish  
 MGU                    Marine grade undercoat  
 NTB                    Natural bronze (premium finish)  
 RAL                    RAL finish



**Wall luminaire · Light emission on two sides**

	LED	A	B	C
<b>B33344</b>	11.8W	13 <sup>7</sup> / <sub>8</sub>	5 <sup>1</sup> / <sub>2</sub>	7 <sup>3</sup> / <sub>8</sub>

