


BEGA

Photometric Filename: 33378.IES

TEST: BE_33378
TEST LAB: BEGA
DATE: 2/14/2017
LUMINAIRE: 33 378
LAMP: 26.6W LED




Characteristics

IES Classification	Type II
Longitudinal Classification	Short
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	3676
Downward Total Efficiency	N.A.
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	115
Total Luminaire Watts	32
Ballast Factor	1.00
Upward Waste Light Ratio	N.A.
Max. Cd.	1684.3 (65H, 52.5V)
Max. Cd. (<90 Vert.)	1684.3 (65H, 52.5V)
Max. Cd. (At 90 Deg. Vert.)	3 (0.1%Lum)
Max. Cd. (80 to <90 Deg. Vert.)	435 (11.8%Lum)
Cutoff Classification (deprecated)	N.A. (absolute)

Lum. Classification System (LCS)


LCS Zone	Lumens	%Lamp	%Lum
FL (0-30)	477.1	N.A.	13.0
FM (30-60)	1286.0	N.A.	35.0
FH (60-80)	582.1	N.A.	15.8
FVH (80-90)	44.6	N.A.	1.2
BL (0-30)	354.2	N.A.	9.6
BM (30-60)	645.0	N.A.	17.5
BH (60-80)	267.4	N.A.	7.3
BVH (80-90)	19.8	N.A.	0.5
UL (90-100)	0.0	N.A.	0.0
UH (100-180)	0.0	N.A.	0.0
Total	3676.3	N.A.	100.0

BUG Rating B1-U0-G1



Mounting Height = 20 ft.

Grid Spacing = 20 ft.



In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2018

3/22/2018