

Application

This wall luminaire has a symmetric light distribution on two sides. The symmetric light distribution can be used to illuminate façade and wall surfaces, with the installation surface also acting as the reflection surface.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Mechanically captive stainless steel fasteners
- High temperature silicone gasket
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Galvanized zinc-plated mounting bracket
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 15.9lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-40° C
LED module wattage	86.8W
System wattage	99.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	9740lm
LED service life (L70)	60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:


BEGA Product:

Project:

Modified:

Available options

CUS	Custom finish
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL Classic, matte finish



Wall washer · Symmetric upward · Symmetric downward				
	LED	A	B	C
B33389	86.8W	12 ⁷ / ₈	7 ¹ / ₈	8 ⁵ / ₈