

Application

Wall luminaire has an unshielded light distribution for general purpose illumination for interior and exterior locations. Arranged individually or in groups, this is a great design element for a host of lighting applications.

Materials

Pressed crystal glass with white ceramic coating on one side  
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 65

**Weight:** 4.0 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	5.6W
System wattage	8.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	609lm
LED service life (L70)	60000hrs

LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:


BEGA Product:

Project:

Modified:

Available options

CUS	Custom finish
DALI-2	Enabled for DALI control system
FSC	Fusing
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL finish



Wall luminaire · Unshielded

		LED	A	B	C
<b>B33601</b>	<b>ADA</b>	5.6W	6 <sup>3</sup> / <sub>4</sub>	6 <sup>3</sup> / <sub>4</sub>	2 <sup>3</sup> / <sub>4</sub>

**BEGA** 1000 BEGA Way, Carpinteria, CA 93013 (805)684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com  
© copyright BEGA 2025 Updated 08/18/25