

Application
Ceiling and wall luminaire with shallow profile designed for general purpose illumination featuring three-ply opal glass. This luminaire can be utilized individually or in groups for glare-free illumination in interior and exterior spaces.

Materials
Three-ply opal glass with satin matte finish
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 64

Weight: 6.6 lbs.

Electrical	
Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	19.6W
System wattage	23.0W
Controllability	0-10V dimming down to 0.1%
Color rendering index	Ra > 90
Luminaire lumens	2094 lm
LED service life (L70)	60000hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors	
Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:
BEGA Product:
Project:
Modified:

Available options	
CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL finish



Ceiling and wall luminaire · Opal glass				
		LED	A	B
B33681	ADA	19.6 W	12	2 ⁵ / ₈

