


BEGA

Photometric Filename: 33817.IES

TEST: BE_33817
TEST LAB: BEGA
DATE: 01/15/2015
LUMINAIRE: 33 817
LAMP: 13.9W LED




Characteristics

IES Classification	Type II
Longitudinal Classification	Very Short
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1355
Downward Total Efficiency	N.A.
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	80
Total Luminaire Watts	17
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Max. Cd.	1195.879 (0H, 35V)
Max. Cd. (<90 Vert.)	1195.879 (0H, 35V)
Max. Cd. (At 90 Deg. Vert.)	0 (0.0%Lum)
Max. Cd. (80 to <90 Deg. Vert.)	49.381 (3.6%Lum)
Cutoff Classification (deprecated)	N.A. (absolute)

Lum. Classification System (LCS)


LCS Zone	Lumens	%Lamp	%Lum
FL (0-30)	255.4	N.A.	18.8
FM (30-60)	718.8	N.A.	53.0
FH (60-80)	186.8	N.A.	13.8
FVH (80-90)	2.9	N.A.	0.2
BL (0-30)	86.1	N.A.	6.4
BM (30-60)	86.8	N.A.	6.4
BH (60-80)	17.9	N.A.	1.3
BVH (80-90)	0.6	N.A.	0.0
UL (90-100)	0.0	N.A.	0.0
UH (100-180)	0.0	N.A.	0.0
Total	1355.3	N.A.	100.0

BUG Rating B0-U0-G0



Wall Mount - Isofootcandle grid on wall

Grid Spacing = 2.5 ft.



Wall Mount - Isofootcandle grid on floor

Mounting Height = 10 ft.

Grid Spacing = 10 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2017

8/17/2017