

Application

Ceiling and wall luminaires designed for the illumination of rooms, bathrooms, stairways, and other interior spaces characterized by their shallow projection featuring hand-blown, three-ply opal glass with satin matte finish.

Materials

- Hand-blown opal glass
- Aluminum housing
- Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, for interior use only

Weight: 6.0 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage16.4 W
- System wattage18.9 W
- Controllability0-10V dimmable
- Color rendering indexRa > 90
- Luminaire lumens1601 lm
- LED service life (L70)60000 hrs

LED color temperature


- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

White finish. Custom colors not available.

Type:  
BEGA Product:  
Project:  
Modified:



Ceiling and wall luminaire · Opal glass					
		LED	A	B	C
B34287	ADA	16.4 W	13 <sup>3</sup> / <sub>8</sub>	3 <sup>3</sup> / <sub>8</sub>	10 <sup>1</sup> / <sub>2</sub>

