

Application

LED semi-recessed luminaires with broad spread light distribution. The distinctive hand-blown, three-ply opal glass with concave interior surface provides a soft uniform light gradient.

Materials

Luminaire housing constructed of die-cast aluminum alloy
 Three-ply opal glass satin matte finish
 Stainless steel screw clamps
 Ceiling mounted driver enclosure constructed of aluminum, a minimum of 7" ceiling clearance is required for installation

NRTL listed to North American Standards, suitable for damp locations
 Weight: 2.2lbs

Electrical


Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	9.6W
System wattage	12.0W
Controllability	0-10V dimming down to 0.1%
Color rendering index	Ra > 90
Luminaire lumens	1,098 lumens (3000K)
Lifetime at Ta = 15° C	50,000 h (L70)

LED color temperature

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Type:
 BEGA Product:
 Project:
 Modified:



Interior LED semi-recessed ceiling luminaires · broad spread light distribution

	LED	A	B	C
34562	9.6W	6 ¼	2	2

