

Application

This unshielded wall luminaire is made of stainless steel and hand-blown, three-ply opal glass. Arranged individually or in groups, it is a great design element for a host of lighting applications.

Materials

- Hand-blown three-ply opal glass
- 316 grade stainless steel
- High temperature silicone gasket
- Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 44

Weight: 2.0lbs.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-30° C
- LED module wattage1.9W
- System wattage5.0W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens285lm
- LED service life (L70)60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:

BEGA Product:

Project:


Modified:

Available options

- FSC
- Fusing

Included (available for pre-shipment)

- B19538
- Small opening wiring box



Wall luminaire · Unshielded						
		LED	A	B	C	D
B44009	ADA	1.9 W	2 <sup>3</sup> / <sub>4</sub>	14 <sup>7</sup> / <sub>8</sub>	4	3

