

Application
The wall mounted luminaire has light output on two sides. Arranged individually or in groups, this is a great design element for a host of lighting applications.

Materials
Clear safety glass with matte finish
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 28.0lbs.

Electrical
Operating voltage 120-277VAC
Minimum start temperature -30° C
LED module wattage 30.4 W
System wattage 36.0 W
Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 2123 lm
LED service life (L70) 60000hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:
BEGA Product:
Project:
Modified:

Available options

CUS	Custom finish
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL finish

Included (available for pre-shipment)
B19537 Narrow opening wiring box



Wall luminaire · Light emission on two sides				
	LED	A	B	C
B44438	30.4 W	59 ⁷ / ₈	4 ¹ / ₈	5

