

**Application**  
Ceiling and wall luminaires designed for general purpose illumination for interior locations featuring a shallow depth and hand-blown, three-ply opal glass with satin matte finish.

**Materials**  
Hand-blown opal glass  
Aluminum housing  
Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, for interior use only

**Weight:** 4.0lbs.

**Electrical**

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	16.8W
System wattage	19.3W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	1718lm
LED service life (L70)	60000hrs

**LED color temperature**

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details


**Finish**  
White finish. Custom colors not available.

Type:  
BEGA Product:  
Project:  
Modified:

**Available accessories**

B13076	Trim ring · White
B13077	Trim ring · Stainless steel
B13078	Trim ring · Chrome

See individual accessory spec sheet for details.



Ceiling and wall luminaire · Opal glass				
		LED	A	B
B50078	ADA	16.8 W	9 <sup>7</sup> / <sub>8</sub>	3 <sup>1</sup> / <sub>8</sub>

