

**Application**  
Ceiling and wall luminaires designed for general purpose illumination for interior locations featuring a shallow depth and hand-blown, three-ply opal glass with satin matte finish.

**Materials**  
Hand-blown opal glass  
Aluminum housing  
Galvanized zinc-plated mounting bracket  
**NRTL** listed to North American Standards, for interior use only

**Weight:** 4.6 lbs.

**Electrical**  
Operating voltage                   120-277VAC  
Minimum start temperature       -30° C  
LED module wattage               25.9 W  
System wattage                    31.2 W  
Controllability                    0-10V dimming down to 1%  
Color rendering index             Ra > 80  
Luminaire lumens                  2479 lm  
LED service life (L70)           60000 hrs


**LED color temperature**  
4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**  
White finish. Custom colors not available.

Type:  
BEGA Product:  
Project:  
Modified:

**Available accessories**  
B13079       Trim ring · White  
B13080       Trim ring · Stainless steel  
B13081       Trim ring · Chrome  
See individual accessory spec sheet for details.



Ceiling and wall luminaire · Opal glass				
		LED	A	B
B50079	ADA	25.9 W	13 <sup>3</sup> / <sub>8</sub>	3 <sup>1</sup> / <sub>2</sub>

