

Application

LED technology and our own LED module production facilities enable us to pursue new avenues of luminaire design and to develop distinctive luminaires in special sizes. These unusual lengths open up new and creative options in many areas of interior design. The luminaires can be mounted in horizontal or vertical orientations.

Materials

White UV-stabilized acrylic diffuser

Aluminum housing

NRTL listed to North American Standards, for interior use only

Weight: 10.8lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-20° C
LED module wattage	70.4 W
System wattage	80.0 W
Controllability	0-10V dimming down to 0.1%
Color rendering index	Ra > 80
Luminaire lumens	9670 lm
LED service life (L70)	60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

White (.1) Matte aluminum (.2)

Type:

BEGA Product:

Project:

Modified:



Linear ceiling and wall luminaire · Unshielded

		LED	A	B	C
B50144	ADA	70.4 W	80 ³ / ₄	2	3 ¹ / ₈

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2024 Updated 08/02/24

Included (available for pre-shipment)

B19537 Narrow opening wiring box