



BEGA

File: 50167K4_BEGA_IES.ies

TEST: BE_50167K4
TEST LAB: BEGA
DATE: 09/15/2015
LUMINAIRE: 50 167K4
LAMP: 8.4W LED





Characteristics

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	777
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	71
Total Luminaire Watts	11
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	0.62
Spacing Criterion (90-270)	0.62
Spacing Criterion (Diagonal)	0.72
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	0.25 ft
Luminous Width (90-270)	0.25 ft
Luminous Height	0.29 ft

Zonal Lumen Summary

Zone	Lumens
0-10	125.20
10-20	259.80
20-30	243.16
30-40	127.23
40-50	16.65
50-60	3.23
60-70	1.23
70-80	0.50
80-90	0.02
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00



Mounting Height: 10 ft.

Grid Spacing: 3 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.



BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2020

07/24/20

BEGA

File: 50167K35_BEGA_IES.ies

TEST: BE_50167K4
TEST LAB: BEGA
DATE: 09/15/2015
LUMINAIRE: 50 167K35
LAMP: 8.4W LED





Characteristics

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	763
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	69
Total Luminaire Watts	11
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	0.62
Spacing Criterion (90-270)	0.62
Spacing Criterion (Diagonal)	0.72
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	0.25 ft
Luminous Width (90-270)	0.25 ft
Luminous Height	0.29 ft

Zonal Lumen Summary

Zone	Lumens
0-10	122.94
10-20	255.13
20-30	238.79
30-40	124.94
40-50	16.35
50-60	3.17
60-70	1.21
70-80	0.49
80-90	0.02
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00



Mounting Height: 10 ft.

Grid Spacing: 3 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.



BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2020

07/24/20

BEGA

File: 50167K3_BEGA_IES.ies

TEST: BE_50167K4
TEST LAB: BEGA
DATE: 09/15/2015
LUMINAIRE: 50 167K3
LAMP: 8.4W LED





Characteristics

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	750
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	68
Total Luminaire Watts	11
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	0.62
Spacing Criterion (90-270)	0.62
Spacing Criterion (Diagonal)	0.72
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	0.25 ft
Luminous Width (90-270)	0.25 ft
Luminous Height	0.29 ft

Zonal Lumen Summary

Zone	Lumens
0-10	120.82
10-20	250.71
20-30	234.65
30-40	122.78
40-50	16.07
50-60	3.11
60-70	1.19
70-80	0.48
80-90	0.02
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00



Mounting Height: 10 ft.

Grid Spacing: 3 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.


BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2020

07/24/20

BEGA

File: 50167K27_BEGA_IES.ies

TEST: BE_50167K4
TEST LAB: BEGA
DATE: 09/15/2015
LUMINAIRE: 50 167K27
LAMP: 8.4W LED





Characteristics

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	744
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	68
Total Luminaire Watts	11
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	0.62
Spacing Criterion (90-270)	0.62
Spacing Criterion (Diagonal)	0.72
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	0.25 ft
Luminous Width (90-270)	0.25 ft
Luminous Height	0.29 ft

Zonal Lumen Summary

Zone	Lumens
0-10	119.94
10-20	248.89
20-30	232.95
30-40	121.89
40-50	15.95
50-60	3.09
60-70	1.18
70-80	0.48
80-90	0.02
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00



Mounting Height: 10 ft.

Grid Spacing: 3 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2020

07/24/20